

VUBA FOUNDATION CAP



PRODUCT SPECIFICATION

PRODUCT DESCRIPTION

VubaFoundationCap is a clean, open-graded primary aggregates used as a blinding layer over the structural sub-base to provide a stable, free-draining platform beneath VUBA's resin-bound system.

INTENDED APPLICATIONS

- Domestic Driveways
- Footpaths and walkways
- Patios and terraces
- Commercial landscaping
- Car Parks
- Adopted infrastructure
- Highways

LIMITATIONS

VubaFoundationCap is intended for use as a capping layer over the structural sub-base and a depth of 25mm. For adoptable highways, the complete project should be designed in accordance with the relevant highway authority or project specifications.

BENEFITS

- Consistent & level working platform
- Promotes rapid water infiltration
- Suitable beneath resin-bound surfacing systems when the specifications of the base build up is followed

TECHNICAL CHARACTERISTICS

PROPERTY	DATA
Product Name	VubaFoundationCap
Material	Angular Limestone/Granite/Sandstone/Hardstone
	Crushed concrete & bricks
Aggregate Size	4/10mm
Grading	Open-Graded
Fines Content	<1%
Drainage	Free draining
Colour	Natural aggregate (may vary)
Typical Supply	Bulk Loose / Bulk Bags

QUALITY ASSURANCE & TESTING

All VubaFoundation aggregates shall be free from contamination such as wood, asphalt, metal, plastic and other materials. VubaFoundationCap should meet BS EN 13242 Aggregate for unbound materials.

***Test certificates available on request.**