

VUBA FOUNDATION (SECONDARY)



PRODUCT SPECIFICATION

PRODUCT DESCRIPTION

VubaFoundation40 (Secondary) is a 20-40mm washed, open-graded recycled aggregate with no fines designed to provide a free-draining foundation for resin bound surfacing and other permeable hard landscaping applications.

INTENDED APPLICATIONS

- Domestic Driveways
- Footpaths and walkways
- Patios and terraces
- Commercial landscaping
- Private car parks
- Private roads

LIMITATIONS

VubaFoundation40 (Secondary) is intended for domestic and commercial off-highway applications. It is not represented as a specification for Highway Works Type 3 materials and should not be specified where compliance with highways specifications is required.

BENEFITS

- Excellent permeability
- Promotes rapid water infiltration
- Supports sustainable construction
- Manufactured using recycled materials
- Suitable beneath resin-bound surfacing systems when the specifications of the base build up is followed

TECHNICAL CHARACTERISTICS

PROPERTY	DATA
Product Name	VubaFoundation40 (Secondary)
Material	Washed crushed concrete & bricks
Aggregate Size	20-40mm
Grading	Open-Graded
Fines Content	<1%
Drainage	Free draining
Colour	Natural recycled aggregate (may vary)
Typical Supply	Bulk Loose / Bulk Bags

QUALITY ASSURANCE & TESTING

All VubaFoundation aggregates shall be tested to verify mechanical performance and consistency. Aggregates shall comply with the following minimum mechanical performance requirements.

TEST	REQUIREMENT
Aggregate Crushing Value (ACV)	<30%
Los Angeles Abrasion (LA)	<45%

***Test certificates available on request.**